



Frequency : 50Hz  
 Fuel Type : Diesel

## COOL POWER GENSET

### TECHNICAL DATA



**Model**                    **CPC245/CPC265E**

Standby power            212kW /    265kVA

Prime power              196kW /    245kVA

Fuel consumption	Standby				Prime			
	kW (kVA)				kW (kVA)			
Ratings	212(265)				196 ( 245 )			
Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full
US gph	N.A	N.A	N.A	N.A	N.A	N.A	N.A	N.A
L/hr	N.A	N.A	N.A	58	15	27	39	53

#### Engine

Engine manufacturer	DCEC
Engine model	6LTAA8.9-G2
Configuration	4-Cycle;In line; 6-Cylinder Diesel
Aspiration	Turbocharged and air to air cooled
Gross engine power output -- kWm	240
BMEP at set rated load -- kPa	N/A
Bore -- mm	114
Stroke -- mm	145
Rated speed -- rpm	1500
Piston speed -- m/s	7.3
Compression ratio	16.6:1
Lube oil capacity -- L	28
Overspeed limit -- rpm	N/A
Regenerative power -- kWm	N/A
Governor type	Electrical
Starting voltage	24 Volts DC

#### Fuel flow

Recommended fuel	ASTM NO.2-D
Governor Type	Electrical
Max fuel transfer pump suction--(m)	2.0

#### Oil system

Oil system capacity--(L)	28
Recommended oil	API-CD OR BETTER
Oil normal temperature--(°C)	121
Oil consumption at 100%	0.26

#### Air

Combustion air -- m <sup>3</sup> /min	14.88/15.2
---------------------------------------	------------

#### Exhaust

Exhaust flow--(m <sup>3</sup> /min)	35.04/38.04
Exhaust temperature--(°C)	≤470
Allowable restriction--(kPa)	10

Exhaust pipe diameter--(mm)	102
-----------------------------	-----

**Standard set-mounted radiator cooling**

Radiator and engine capacity--(L)	40
Fan power--(kW)	8.8
Fan Air flow--(m <sup>3</sup> /min)	450
Coolant normal temperature--(°C)	83-95
Max water temperature--(°C)	110
Type of coolant	Glycol

**Alternator**

Alternator manufacturer	Stamford
Alternator model	UCDI274K
Control System	Self Excited and Brushless
Insulation class	H
Temperature Rise	H
Rated Power Factor	0.8
Winding Pitch	Two Thirds
Voltage adjust scope	≥ ±5%
Weight--(kg)	727
A.V.R.	AS440
Protection	IP 23
Stator Winding	Double layer Concentric
Winding Leads	12
Voltage regulation	≤ ±10%
Bearing number	1
Cooling Air--(m <sup>3</sup> /sec)	0.58

**Weights\***

	Open	Enclosed
Unit wet weight kgs	1990	2030

\* Weights represent a set with standard features. See outline drawing for weights of other configurations

**Dimensions**

	Length "A"	Width "B"	Height "C"
Standard open set dimensions, mm	2575	1000	1800

**Control Panel**

Manual Control Panel:	Auto Control Panel:	Remote control Panel:
Manual start	Manual and auto start	All the parameter can display on LCD screen
Voltage, Current, Frequency, Battery voltage, Hour meter, Charger Alternator Voltage and Speed(R.P.M) can be displayed by means of LCD	The parameter of Voltage, Current, Frequency, Battery voltage, Hour meter, Charger Alternator Voltage and Speed(R.P.M) can be displayed on LCD screen	It includes all the function of manual and auto control panel.
Emergency stop pushbutton	Emergency stop push button	Detect RPM of the gen-set, active power, power factor and so on. It also can detect main parameter, include main voltage, main frequency. Event and performance log

See your distributor for more information.

COOLTECH POWER INTERNATIONAL PTE. LTD.  
 Add: 22 Boon Lay Way #01-64, Tradehub 21, Singapore 609968  
 Tel: +65-67957003 Fax: +65-67957013  
 Website: [www.generators.com.sg](http://www.generators.com.sg)

The above information is only for reference purpose and shall constitute no restraint to us. No further notice shall be given upon any change of the information, We reserve the authority for final revision.