



Frequency : 50Hz  
 Fuel Type : Diesel

# COOL POWER GENSET

## TECHNICAL DATA



**Model**                    **CPC550E**  
 Standby power        440kW /    550kVA  
 Prime power           400kW /    500kVA

Fuel consumption	Standby				Prime			
	kW (kVA)				kW (kVA)			
Ratings	440(550)				400 (500)			
Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full
US gph	N.A	N.A	N.A	N.A	N.A	N.A	N.A	N.A
L/hr	N.A	N.A	N.A	123	30.3	54.7	78.7	103

### Engine

Engine manufacturer	Cummins
Engine model	QSX15-G8 (Made in USA)
Configuration	4-Cycle; In-line; 6-Cylinder Diesel
Aspiration	Turbocharged and Charge Air Cooled
Gross engine power output -- kWm	500
BMEP at set rated load -- kPa	2675
Bore -- mm	137
Stroke -- mm	169
Rated speed -- rpm	1500
Piston speed -- m/s	8.4
Compression ratio	17:1
Lube oil capacity -- L	91
Overspeed limit -- rpm	1800 ±50
Regenerative power -- kWm	40
Governor type	Electronic
Starting voltage	24 Volts DC

### Fuel flow

Recommended fuel	ASTM NO.2-D
Governor Type	Electronic
Max fuel transfer pump suction--(m)	0.9

### Oil system

Oil system capacity--(L)	91
Recommended oil	API-CD OR BETTER
Oil normal temperature--(°C)	121
Oil consumption at 100%	0.62

### Air

Combustion air -- m <sup>3</sup> /min	36.3
---------------------------------------	------

### Exhaust

Exhaust flow--(m <sup>3</sup> /min)	82.2
Exhaust temperature--(°C)	≤515
Allowable restriction--(kPa)	10

Exhaust pipe diameter--(mm)	159
-----------------------------	-----

### Standard set-mounted radiator cooling

Radiator and engine capacity--(L)	94
Fan power--(kW)	17
Fan Air flow--(m <sup>3</sup> /min)	690
Coolant normal temperature--(°C)	82-93
Max water temperature--(°C)	104
Type of coolant	Glycol

### Alternator

Alternator manufacturer	Stamford
Alternator model	HCI544D
Control System	Self Excited and Brushless
Insulation class	H
Temperature Rise	H
Rated Power Factor	0.8
Winding Pitch	Two Thirds
Voltage adjust scope	≥ ±5%
Weight--(kg)	1393
A.V.R.	AS440
Protection	IP 23
Stator Winding	Double layer Concentric
Winding Leads	12
Voltage regulation	≤ ±10%
Bearing number	1
Cooling Air--(m <sup>3</sup> /sec)	1.035
Voltage (v)	380v/220v

### Weights\*

	Open	Enclosed
Unit wet weight kgs	4080	N.A.

\* Weights represent a set with standard features. See outline drawing for weights of other configurations

### Dimensions

	Length "A"	Width "B"	Height "C"
Standard open set dimensions, mm	3360	1400	2185

### Control Panel

Manual Control Panel:	Auto Control Panel:	Remote control Panel:
Manual start	Manual and auto start	All the parameter can display on LCD screen
Voltage, Current, Frequency, Battery voltage, Hour meter, Charger Alternator Voltage and Speed(R.P.M) can be displayed by means of LCD	The parameter of Voltage, Current, Frequency, Battery voltage, Hour meter, Charger Alternator Voltage and Speed(R.P.M) can be displayed on LCD screen	It includes all the function of manual and auto control panel.
Emergency stop pushbutton	Emergency stop push button	Detect RPM of the gen-set, active power, power factor and so on.
		It also can detect main parameter, include main voltage, main frequency.
		Event and performance log

See your distributor for more information.

COOLTECH POWER INTERNATIONAL PTE. LTD.  
 Add: 22 Boon Lay Way, #01-64, Tradehub 21, Singapore 609968  
 Tel: +65-67957003 Fax: +65-67957013  
 Website: [www.generators.com.sg](http://www.generators.com.sg)