



Frequency : 50Hz  
 Fuel Type : Diesel

# COOL POWER GENSET

## TECHNICAL DATA



**Model CPV140E**  
 Standby power 112kW / 140kVA  
 Prime power 100kW / 125kVA

Fuel consumption	Standby				Prime			
	kW (kVA)				kW (kVA)			
Ratings	112(140)				100(125)			
Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full
US gph	N.A	N.A	N.A	N.A	N.A	N.A	N.A	N.A
L/hr	7.5	14	21	28.5	7.0	12.5	18.5	25

Engine	
Engine manufacturer	VOI VO
Engine model	TAD532GE
Configuration	4-Cycle; In-line;4-Cylinder Diesel
Aspiration	Turbocharged
Gross engine power output -- kWm	130
BMEP at set rated load -- kPa	2200
Bore -- mm	108
Stroke -- mm	130
Rated speed -- rpm	1500
Piston speed -- m/s	6.5
Compression ratio	18:1
Lube oil capacity -- L	13
Overspeed limit -- rpm	1800
Regenerative power -- kWm	13
Governor type	Mechanical
Starting voltage	24 Volts DC

Fuel flow	
Recommended fuel	ASTM NO.2-D
Governor Type	Mechanical
Max fuel transfer pump suction--(m)	0.9

Oil system	
Oil system capacity--(L)	13
Recommended oil	API-CF-4 OR BETTER
Oil normal temperature--(°C)	110
Oil consumption at 100%( L/hr)	0.08

Air	
Combustion air -- m <sup>3</sup> /min	8.03

Exhaust	
Exhaust flow--(m <sup>3</sup> /min)	23.2
Exhaust temperature--(°C)	532
Allowable restriction--(kPa)	5

The above information is only for reference purpose and shall constitute no restraint to us. No further notice shall be given upon any change of the information, We reserve the authority for final revision.

Exhaust pipe diameter--(mm)	76
-----------------------------	----

**Standard set-mounted radiator cooling**

Radiator and engine capacity--(L)	22
Fan power--(kW)	8
Fan Air flow--(m <sup>3</sup> /min)	174
Coolant normal temperature--(°C)	83-95
Max water temperature--(°C)	105
Type of coolant	Glycol

**Alternator**

Alternator manufacturer	Stamford
Alternator model	UCI274E
Control System	Self Excited and Brushless
Insulation class	H
Temperature Rise	H
Rated Power Factor	0.8
Winding Pitch	Two Thirds
Voltage adjust scope	≥ ± 5%
Weight--(kg)	492
A.V.R.	AS440
Protection	IP 23
Stator Winding	Double layer Concentric
Winding Leads	12
Voltage regulation	≤ ± 1%
Bearing number	1
Cooling Air--(m <sup>3</sup> /sec)	0.514
Voltage (v)	400/230

**Weights\***

	Open	Enclosed
Unit wet weight kgs	1400	N.A.

\* Weights represent a set with standard features. See outline drawing for weights of other configurations

**Dimensions**

	Length "A"	Width "B"	Height "C"
Standard open set dimensions, mm	2200	875	1640

**Control Panel**

Manual Control Panel:	Auto Control Panel:	Remote control Panel:
Manual start Voltage, Current, Frequency, Battery voltage, Hour meter, Charger Alternator Voltage and Speed(R.P.M) can be displayed by means of LCD Emergency stop pushbutton	Manual and auto start The parameter of Voltage, Current, Frequency, Battery voltage, Hour meter, Charger Alternator Voltage and Speed(R.P.M) can be displayed on LCD screen Emergency stop push button	All the parameter can display on LCD screen It includes all the function of manual and auto control panel. Detect RPM of the gen-set, active power, power factor and so on. It also can detect main parameter, include main voltage, main frequency. Event and performance log

See your distributor for more information.

COOLTECH POWER INTERNATIONAL PTE. LTD.  
 Add: 22 Boon Lay Way, #01-64 Tradehub 21, Singapore 609968  
 Tel: +65-67957003 Fax: +65-67957013  
 Website: [www.generators.com.sg](http://www.generators.com.sg)

The above information is only for reference purpose and shall constitute no restraint to us. No further notice shall be given upon any change of the information, We reserve the authority for final revision.