



Frequency : 50Hz
 Fuel Type : Diesel

COOL POWER GENSET

TECHNICAL DATA



Model CPV90E

Standby power 90kW / 72kVA
 Prime power 80kW / 64kVA

Fuel consumption	Standby				Prime			
	kW (kVA)				kW (kVA)			
Ratings	72(90)				64(80)			
Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full
US gph	N.A	N.A	N.A	N.A	N.A	N.A	N.A	N.A
L/hr	6.9	12	17.3	23	6.5	11	15.5	21

Engine

Engine manufacturer	VOI VO
Engine model	TAD530GE
Configuration	4-Cycle; In-line;4-Cylinder Diesel
Aspiration	Turbocharged
Gross engine power output -- kWm	89
BMEP at set rated load -- kPa	1500
Bore -- mm	108
Stroke -- mm	130
Rated speed -- rpm	1500
Piston speed -- m/s	6.5
Compression ratio	18:1
Lube oil capacity -- L	13
Overspeed limit -- rpm	1800
Regenerative power -- kWm	9
Governor type	Mechanical
Starting voltage	24 Volts DC

Fuel flow

Recommended fuel	ASTM NO.2-D
Governor Type	Mechanical
Max fuel transfer pump suction--(m)	0.9

Oil system

Oil system capacity--(L)	13
Recommended oil	API-CD OR BETTER
Oil normal temperature--(°C)	110
Oil consumption at 100%	0.08

Air

Combustion air -- m ³ /min	5.54
---------------------------------------	------

Exhaust

Exhaust flow--(m ³ /min)	16.3
Exhaust temperature--(°C)	540
Allowable restriction--(kPa)	5

Exhaust pipe diameter--(mm)	76
-----------------------------	----

Standard set-mounted radiator cooling

Radiator and engine capacity--(L)	22
Fan power--(kW)	5.9
Fan Air flow--(m ³ /min)	120
Coolant normal temperature--(°C)	83-95
Max water temperature--(°C)	105
Type of coolant	Glycol

Alternator

Alternator manufacturer	Stamford
Alternator model	UCI224G
Control System	Self Excited and Brushless
Insulation class	H
Temperature Rise	H
Rated Power Factor	0.8
Winding Pitch	Two Thirds
Voltage adjust scope	≥ ± 5%
Weight--(kg)	383
A.V.R.	AS440
Protection	IP 23
Stator Winding	Double layer Concentric
Winding Leads	12
Voltage regulation	≤ ± 1%
Bearing number	1
Cooling Air--(m ³ /sec)	0.216
Voltage (v)	400/230

Weights*

	Open	Enclosed
Unit wet weight kgs	1310	N.A.

* Weights represent a set with standard features. See outline drawing for weights of other configurations

Dimensions

	Length "A"	Width "B"	Height "C"
Standard open set dimensions, mm	2020	850	1540

Control Panel

Manual Control Panel:	Auto Control Panel:	Remote control Panel:
Manual start	Manual and auto start	All the parameter can display on LCD screen
Voltage, Current, Frequency, Battery voltage, Hour meter, Charger Alternator Voltage and Speed(R.P.M) can be displayed by means of LCD	The parameter of Voltage, Current, Frequency, Battery voltage, Hour meter, Charger Alternator Voltage and Speed(R.P.M) can be displayed on LCD screen	It includes all the function of manual and auto control panel.
Emergency stop pushbutton	Emergency stop push button	Detect RPM of the gen-set, active power, power factor and so on.
		It also can detect main parameter, include main voltage, main frequency.
		Event and performance log

See your distributor for more information.

COOLTECH POWER INTERNATIONAL PTE. LTD.
 Add: 22 Boon Lay Way, #01-64 Tradehub 21, Singapore 609968
 Tel: +65-67957003 Fax: +65-67957013
 Website: www.generators.com.sg